

**SPECIFICATION OF
200W.220W MONO SOLAR MODULE**

Mono-Crystalline

Module type	Pm(W)	Number of cell	Cell Dimension (mm)	Max System Voltage(V)	Vm(V)	Im(A)	Voc(V)	Isc(A)
SM200	200W	91	125	1000	44.8	4.47	50.3	5.2
SM220	220W	91	125	1000	47.5	4.63	53.7	5.37

Parameter

Maximum system voltage (V)	1000
Temperature coefficients of Isc (%)	+0.1%/°C
Temperature coefficients of Voc (%)	-0.38%/°C
Temperature coefficients of Pm (%)	-0.47%/°C
Temperature coefficients of Im (%)	+0.1%/°C
Temperature coefficients of Vm (%)	-0.38%/°C
Temperature Range	-40°C ---85°C
Tolerance Wattage (e.g. +/-5%)	± 5%
Surface Maximum Load Capacity	60m/s (200kg/sq.m)
Junction Box Type	PPO, black
Connectors and Cables Type	4mm2
Length of Cables (mm)	900
Cell Efficiency (%)	>16.8%
Output tolerance (%)	± 5%
Frame (Material, Corners, etc.)	Anodized Aluminum Alloy
Standard Test Conditions	AM1.5 100MW/cm² 25°C
Guarantee of power	2 years for whole products,90% power for 10years, 80% power for 25years.
FF (%)	≥73.3%



Physical Characters

Output	Module Net Weight	Module Size (MM)	Packing	20' Container	40' Container
200W	19.0(kg)	1702*945*45	2pcs/carton	226 pcs	488 pcs
220W	19.0(kg)	1702*945*45	2pcs/carton	226 pcs	488 pcs